



Features & benefits ↓

- Compact
- Lightweight
- Usable in all positions
- Safe; no flying off parts or sparks
- Adjustable blade; prevents damage to the thread

Standard supplied with ↓

- High Flow female coupler A 118
- Plastic carrying box, including:
 - High-grade grease Molycote®
 - Spare blade

Hydraulic Pumps	page	139
Hydraulic Hoses	page	166
Pressure Gauges	page	171



Adjustable blade; prevents damage to the thread



Nut Splitters - Spring Return



model	HNC 1536 NU		HNC 3250 U	
art no	100.102.009		100.102.006	
max. working pressure	bar/Mpa	720 / 72	720 / 72	
min. reach bolt	M12 (1/2")		M22 (7/8")	
max. reach category 8 bolt	M24 (7/8")		M33 (1 1/4")	
max. reach 2H bolt	M20 (3/4")		M33 (1 1/4")	
capacity	kN/t	148 / 15.1	316 / 32.2	
required oil content (effective)	cc	32	57	
return type	spring		spring	
weight, ready for use	kg	2.9	7.2	
weight, incl. case	kg	4.2	8.6	
thickness cutting head	mm	23	33	

Nut Splitters - Spring Return (dimensions)



model	HNC 1536 NU		HNC 3250 U	
dimension A	mm	86	118	
dimension B	mm	11	19	
dimension C	mm	104	139	
dimension D	mm	277	321	

