

ÇALIŞMA YÜK KAPASİTELERİ (TON) - Grade 10

Sapan tipi	1 bacaklı					2 bacaklı				3 & 4 bacaklı			
	Direkt	0-45°	45-60°	Asimetrik yük	Tek bacak	0-45°	45-60°	Asimetrik yük	Tek bacak				
Zincir ölçüsü	1	1.4	1	1	1	2.1	1.5	1	1				
6	1.5	2.1	1.5	1.5	1.5	3.15	2.24	1.5	1.5				
7	2.0	1.8	2.0	2.0	2.0	4.2	3.0	2.0	2.0				
8	2.5	3.5	2.5	2.5	2.5	5.25	3.7	2.5	2.5				
10	4.0	5.6	4.0	4.0	4.0	8.40	6.0	4.0	4.0				
13	6.7	9.5	6.7	6.7	6.7	14.0	10.0	6.7	6.7				
16	10.0	14.0	10.0	10.0	10.0	21.0	15.0	10.0	10.0				
20	16.0	22.4	16.0	16.0	16.0	33.6	24.0	16.0	16.0				
22	20.0	28.0	20.0	20.0	20.0	42.0	30.0	20.0	20.0				
26	27.0	38.2	27.0	27.0	27.0	57.3	40.5	27.0	27.0				

Sapan tipi	1 bacaklı					2 bacaklı Boğma kancalı				Dahili cep ilmiği			
	Direkt	0-45°	45-60°	Asimetrik yük	Tek bacak	max 30°	45° max 30°	45° max 30°	45° max 30°				
Zincir ölçüsü	0.8	1.1	0.8	0.8	0.8	1	1.4	2.1	2.1				
6	1.2	1.6	1.2	1.2	1.2	1.5	2.12	3.15	3.15				
7	1.6	2.2	1.6	1.6	1.6	2.0	2.8	4.2	4.2				
8	2.0	2.7	2.0	2.0	2.0	2.5	3.5	5.2	5.2				
10	3.2	4.4	3.2	3.2	3.2	4.0	5.6	8.4	8.4				
13	5.2	7.4	5.3	5.3	5.3	6.7	9.5	14.0	14.0				
16	8.0	11.0	8.0	8.0	8.0	10.0	14.0	21.0	21.0				
20	12.8	17.6	12.8	12.8	12.8	-	-	-	-				
22	16.0	22.0	16.0	16.0	16.0	-	-	-	-				
26	21.6	29.7	21.6	21.6	21.6	-	-	-	-				

Sapan tipi	Çember sapanlar				Sonsuz boğma
	0-45°	45-60°	0-45°	45-60°	
Zincir ölçüsü	1.4	1	2.1	1.5	1.6
6	2.1	1.5	3.15	2.24	2.5
7	1.8	2.0	4.2	3.0	3.2
8	3.5	2.5	5.25	3.7	4.0
10	5.6	4.0	8.40	6.0	6.4
13	9.5	6.7	14.0	10.0	10.7
16	14.0	10.0	21.0	15.0	16.0
20	22.4	16.0	33.6	24.0	25.6
22	28.0	20.0	42.0	30.0	32.0
26	38.2	27.0	57.3	40.5	43.2

Grade 8 Classic (ton)

Zincir Ölçüsü mm	1 bacak	2 bacak		3-4 bacak		Sonsuz boğma
	WLL ton*	0-45°	45-60°	0-45°	45-60°	
6	1.1	1.6	1.1	2.36	1.7	1.8
7	1.50	2.12	1.5	3.15	2.24	2.5
8	2.0	2.8	2.0	4.25	3.0	3.15
10	3.15	4.25	3.15	6.7	4.75	5.0
13	5.3	7.5	5.3	11.2	8.0	8.5
16	8.0	11.2	8.0	17.0	11.8	12.5
20	11.2	16.0	11.2	23.6	17.0	18.0
22	15.0	21.2	15.0	31.5	22.4	23.6
26	21.2	30.0	21.2	45.0	31.5	33.5
32	31.5	45.0	31.5	67.0	47.5	50.0